



**KJNN**

JIC MALE 74° CONE / NPT FEMALE/NPT MALE TEE

PART NO.	THREAD			DIMENSIONS					
	E	F	G	A	B	C	S1		
KJNN-04-02-02Z	7/16"X20	Z1/8"X27	Z1/8"X27	26.5	16.8	24.5	16		
KJNN-04Z	7/16"X20	Z1/4"X18	Z1/4"X18	29.5	22.4	28	19		
KJNN-06-04-04Z	9/16"X18	Z1/4"X18	Z1/4"X18	30	22.4	28	19		
KJNN-06Z	9/16"X18	Z3/8"X18	Z3/8"X18	33.5	25.9	33.5	24		
KJNN-08-06-06Z	3/4"X16	Z3/8"X18	Z3/8"X18	36	25.9	33.5	24		
KJNN-08Z	3/4"X16	Z1/2"X14	Z1/2"X14	39.5	31.2	41.2	30		
KJNN-10-08-08Z	7/8"X14	Z1/2"X14	Z1/2"X14	42.5	31.2	41.2	30		
KJNN-12Z	1.1/16"X12	Z3/4"X14	Z3/4"X14	48	34.5	45.2	33		
KJNN-14-12-12Z	1.3/16"X12	Z3/4"X14	Z3/4"X14	48.5	34.5	45.2	33		
KJNN-16Z	1.5/16"X12	Z1"X11.5	Z1"X11.5	55.1	41.1	54.5	41		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	KJNN-08Z
304 stainless steel	SR	KJNN-08SR
316L stainless steel	SV	KJNN-08SV
316Ti stainless steel	SY	KJNN-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	KJNN-08Z	96	360
Durakote plating	ZD	KJNN-08ZD	360	720
Zinc-nickel plating	ZN	KJNN-08ZN	1000	-