



5JT9

JIC MALE 74° CONE/BSPT FEMALE 90° ELBOW

PART NO.	THREAD		DIMENSIONS						
	E	F	A	B	S1				
5JT9-04-02Z	7/16"X20	Rc1/8"X28	27.5	20	16				
5JT9-04Z	7/16"X20	Rc1/4"X19	30	25	19				
5JT9-05-04Z	1/2"X20	Rc1/4"X19	30	25	19				
5JT9-06Z	9/16"X18	Rc3/8"X19	33.5	27	24				
5JT9-06-04Z	9/16"X18	Rc1/4"X19	30.5	25	19				
5JT9-08Z	3/4"X16	Rc1/2"X14	39.5	31.5	30				
5JT9-08-06Z	3/4"X16	Rc3/8"X19	36	27	24				
5JT9-10-08Z	7/8"X14	Rc1/2"X14	42.5	31.5	30				
5JT9-12Z	1.1/16"X12	Rc3/4"X14	48	37	33				
5JT9-12-08Z	1.1/16"X12	Rc1/2"X14	46.2	31.5	30				
5JT9-16Z	1.5/16"X12	Rc1"X11	54	43	41				
5JT9-20Z	1.5/8"X12	Rc1.1/4"X11	62	46	50				
5JT9-24Z	1.7/8"X12	Rc1.1/2"X11	74.5	55	63				

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5JT9-08Z
304 stainless steel	SR	5JT9-08SR
316L stainless steel	SV	5JT9-08SV
316Ti stainless steel	SY	5JT9-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5JT9-08Z	96	360
Durakote plating	ZD	5JT9-08ZD	360	720
Zinc-nickel plating	ZN	5JT9-08ZN	1000	-